

Safety Data Sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: TRANSELAST

1.2 Relevant identified uses of the substance or mixture and uses advised against

No relevant identified uses-mixture of substances.

Application of the substance / the mixture: Waterproofing coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

COLTECH Ltd

Industrial Area of Inofita 32 011 Inofita, Greece

Tel. : +30 211 7709108

Fax: +30 211 7709108

e-mail: info@coltech.gr

website: www.coltech.gr

1.4 Emergency telephone number:



Emergency telephone number: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

(Contd. on page 2)

GB

Page 2/13

Safety Data Sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 1)

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:



GHS02 GHS07 GHS08

Signal word: Danger

Hazard-determining components of labelling:

Xylene

1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

isophorone di-isocyanate

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers

Hazard statements:

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P261 Avoid breathing vapours.

P285 In case of inadequate ventilation wear respiratory protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P331 Do NOT induce vomiting.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)

GB

Page 3/13

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

vPvB: Not applicable.














(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture: consisting of the following components.

Ingredients:

CAS: 1330-20-7 EINECS: 215-535-7 Flam. Liq. 3, H226; Reg.nr.: 01-2119488216-32-XXXX	Xylene  Asp. Tox. 1, H304;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	20-<25%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-0000015906-63-XXXX	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3- oxazolidinyl)ethyl)carbamate  Skin Sens. 1, H317	10-<25%
CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24-XXXX	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers  Skin Sens. 1, H317; STOT SE 3, H335	3-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226	3-<10%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5 Reg.nr.: 01-2119490408-31-XXXX	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate isophorone di-isocyanate  Acute Tox. 1, H330;  Resp. Sens. 1, H334;  Aquatic Chronic 2, H411;  Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.3-1%
CAS: 540-84-1 EINECS: 208-759-1 Index number: 601-009-00-8	2,2,4-trimethylpentane  Flam. Liq. 2, H225;  Asp. Tox. 1, H304;  Aquatic Acute 1, H400; Aquatic Chronic 1, H410;  Skin Irrit. 2, H315; STOT SE 3, H336	0.1-<0.25%

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.
Seek immediate medical advice.

After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 4)

GB

Page 7/13

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 3)

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water.

Protect unharmed eye.

Seek immediate medical advice.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Avoid inhalation of vapors.

Wear protective clothing.

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

(Contd. on page 5)

GB

Page 5/15

Safety Data Sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 4)

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust, silica gel).

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special precautions are necessary if used correctly.

Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Prevent any seepage into the ground.

Provide ventilation for receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

GB

(Contd. on page 6)

Page 6/15

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate isophorone di-isocyanate

WEL Short-term value: 0.07 mg/m³
Long-term value: 0,02 mg/m³
Sen; as -NCO

Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

(Contd. on page 7)

GB

Page 7/15

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:



Safety glasses

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Liquid
Colour:	Transparent
Odour:	Characteristic
Odour threshold:	Not determined

pH value: Not applicable

Melting point/Melting range: Not determined

Boiling point/Boiling range: Not determined

Flash point: 27 °C

Flammability (solid, gaseous): Not applicable

Auto-ignition temperature: Not determined

Decomposition temperature: Not determined

(Contd. on page 8)

GB

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 7)

Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0,7 Vol %
Upper:	7,5 Vol %
Vapour pressure:	Not determined
Density at 20 °C:	1,01 g/cm ³
Relative density	Not determined
Vapour density	Not determined
Evaporation rate	Not determined
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined
Viscosity:	
Dynamic:	Not determined
Kinematic at 20 °C:	>40 s (ISO 2431:1993 ; 6 mm JET)
Solvent content:	
VOC (EC)	330 g/l
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Heat, flames and othe sources of ignition.

10.5 Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

(Contd. on page 9)

GB

Page 7/13

Safety Data Sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 8)

LD/LC50 values relevant for classification:

	ATEmix/vapour	40 mg/l (-)
Dermal	LD50	4545 mg/kg (rabbit) (ATE)
Inhalative	ATEmix/dust/mist	2.72 mg/l (-) (ATE)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8532 mg/kg (rat)
------	------	------------------

1330-20-7 Xylene

Dermal	LD50	>1700 mg/kg (rabbit)
--------	------	----------------------

**4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate
isophorone di-isocyanate**

Oral	LD50	>2645 mg/kg (mouse)
Dermal	LD50	>7000 mg/kg (rat)
Inhalative	LC50/4 h (dust/mist)	0.031 mg/l (rat)

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

(Contd. on page 10)

GB

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 9)

Additional ecological information:**General notes:**

Also poisonous for fish and plankton in water bodies.

The product contains materials that are harmful to the environment.

12.5 Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

*

SECTION 14: Transport information**14.1 UN-Number**

IATA

UN1866

14.2 UN proper shipping name

IATA

RESIN SOLUTION

14.3 Transport hazard class(es)

IATA



Class

3 Flammable liquids.

Label

3

(Contd. on page 11)

GB

Page 11/12

Safety Data Sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 10)

14.4 Packing group

IATA III

14.5 Environmental hazards: Not applicable.

14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Remarks: No goods of grade 3 according to 2.2.3.1.5 ADR and 2.3.2.5 IMDG
ADR: Containers >450 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
IMDG: Containers > 30 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable

IMDG

Remarks: No goods of grade 3 according to 2.2.3.1.5 ADR and 2.3.2.5 IMDG
ADR: Containers >450 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
IMDG: Containers > 30 l = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable
Outside ADR/IMDG = UN 1866 - 3 (F1) - RESIN SOLUTION, flammable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC
Regulation (EU) 2015/830
CLP Regulation 1272/2008/EC

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

(Contd. on page 12)

GB

Page 12/13

Safety Data Sheet

complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 11)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

(Contd. on page 13)

GB

Page 12/12

Safety Data Sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 08.12.2015

Version number 3

Revision: 06.11.2014

Trade name: TRANSELAST

(Contd. of page 12)

Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Acute Tox. 1: Acute toxicity, Hazard Category 1
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
*** Data compared to the previous version altered.**

GB

COLTECH